

RLB800



PREMIUM DEEP TREAD ON/OFF HIGHWAY SEVERE SERVICE DRIVE-POSITION TIRE

- Advanced chip/cut and abrasion resistant compounds for increased mileage.
- Extra deep open shoulder design evacuates mud and soft soil, providing traction even in challenging environments.
- Durable casing construction.



| PRODUCT CODE | TIRE SIZE | PLY RATING | LOAD RANGE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (INCH) | SECTION WIDTH (INCH) | TREAD DEPTH (32NDS) | RIM | SINGLE MAX LOAD/PRESSURE | DUAL MAX LOAD/PRESSURE | STATIC LOAD RADIUS | REVS PER MILE | WEIGHT (LB) |
|--------------|----------------|------------|------------|------------|--------------|-------------------------|----------------------|---------------------|------|--------------------------|------------------------|--------------------|---------------|-------------|
| 1133501026 | 10.00R20 | 16 | H | 146/143 | G | 41.9 | 10.7 | 29 | 7.50 | 6610lb/120psi | 6005lb/120psi | 19.7 | 489 | 130 |
| 1133501027 | 10.00R20 | 18 | J | 149/146 | G | 41.9 | 10.7 | 29 | 7.50 | 7160lb/61psi | 6610lb/61psi | 19.7 | 489 | 130 |
| 1133501256 | 11R22.5 | 16 | H | 148/145 | G | 41.9 | 10.9 | 29 | 8.25 | 6940lb/123psi | 6390lb/123psi | 20.0 | 491 | 132 |
| 1133501456 | 11R24.5 | 16 | H | 149/146 | G | 43.9 | 10.9 | 29 | 8.25 | 7160lb/120psi | 6610lb/120psi | 21.0 | 468 | 141 |
| 1133502258 | 12R22.5 | 18 | J | 152/149 | K | 43.6 | 11.9 | 33 | 9.00 | 7830lb/61psi | 7160lb/61psi | 23.0 | 423 | 160 |
| 1133502250 | 12.00R24 (NHS) | 18 | J | 158/155 | J | 48.4 | 12.3 | 30 | 8.50 | 9370lb/120psi | 8540lb/120psi | 22.7 | 423 | 221 |



Line Haul



Work



Regional



All-Season/Terrain



Fuel Efficient (SmartWay®)



Double Coin manufactures EPA SmartWay®-verified technologies