

REM-8



(MCS) HIGH-SPEED CRANE TIRE

The REM-8 high-speed crane OTR tire is U.S. DOT approved for on-highway use. The OEM Certified REM-8 is designed with a universal tread pattern to help minimize fuel consumption, improve traction and deliver a more comfortable ride.

| PRODUCT CODE | TIRE SIZE | PATTERN | LOAD SYMBOL | SPEED MAX (KM/H) | SPEED MAX (MPH) | OVERALL DIAMETER (INCH) | SECTION WIDTH (INCH) | TREAD DEPTH (32NDS) | RIM | SINGLE MAX LOAD/PRESSURE | TIRE WEIGHT | TIRE TYPE | NOTE |
|--------------|-------------------------|---------|-------------|------------------|-----------------|-------------------------|----------------------|---------------------|-----------|--------------------------|-------------|-----------|------|
| 1117184241 | 14.00R24 (385/95R24) | REM-8 | 170 | E | E | 54 | 16 | 31 | 10.00W | 10800lb/131psi | 133kg/293lb | T/L | - |
| 1117184251 | 14.00R25 (385/95R25) | REM-8 | 170 | F | F | 54 | 16 | 31 | 10.00/1.5 | 13227lb/131psi | 135kg/305lb | T/L | - |
| 1117186251 | 16.00R25 (445/95R25) | REM-8 | 177 | E | E | 59 | 17 | 33 | 11.25/2.0 | 13200lb/131psi | 209kg/446lb | T/L | - |
| 1117196251 | 16.00R25 (445/95R25) | REM-8 | 174 | F | F | 59 | 17 | 33 | 11.25/2.0 | 14800lb/131psi | 203kg/444lb | T/L | - |
| 1117190251 | 20.5R25 (525/80R25) | REM-8 | 179 | E | E | 59 | 21 | 39 | 11.25/2.0 | 15663lb/131psi | 231kg/502lb | T/L | - |