

REM-8



(MCS) HIGH-SPEED CRANE TIRE

The REM-8 high-speed crane OTR tire is U.S. DOT approved for on-highway use. The OEM Certified REM-8 is designed with a universal tread pattern to help minimize fuel consumption, improve traction and deliver a more comfortable ride.



PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/ PRESSURE	TIRE WEIGHT	TIRE TYPE	NOTE
1117184241	14.00R24 (385/95R24)	REM-8	170	E	E	54	16	31	10.00W	10800lb/131psi	133kg/293lb	T/L	-
1117184251	14.00R25 (385/95R25)	REM-8	170	F	F	54	16	31	10.00/1.5	13227lb/131psi	135kg/305lb	T/L	-
1117186251	16.00R25 (445/95R25)	REM-8	177	E	E	59	17	33	11.25/2.0	13200lb/131psi	209kg/446lb	T/L	-
1117196251	16.00R25 (445/95R25)	REM-8	174	F	F	59	17	33	11.25/2.0	14800lb/131psi	203kg/444lb	T/L	-
1117190251	20.5R25 (525/80R25)	REM-8	179	E	E	59	21	39	11.25/2.0	15663lb/131psi	231kg/502lb	T/L	-