

REM-10



(E3/L3) HAULAGE/ARTICULATED TIRE

The OEM Certified REM-10 OTR tire features a multi-function, non-directional tread design for optimum performance. Designed for the rugged needs of articulating trucks, the REM-10 OTR is built with a unique center block tread design, that delivers superior off-the-road traction, and a smooth ride in all types of terrain.



PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	TIRE WEIGHT	TIRE TYPE	NOTE
1087106252	26.5R25	REM-10	★★	50	30	69	27	51	22.00/3.0	25300lb/76psi	463kg/1023lb	T/L	-
1087106252	26.5R25	REM-10	★★	10	5	69	27	51	22.00/3.0	40700lb/94psi	463kg/1023lb	T/L	-
1087102955	29.5R25	REM-10	★★	50	30	74	29	55	25.00/3.5	30800lb/76psi	597kg/1285lb	T/L	-
1087102955	29.5R25	REM-10	★★	10	5	74	29	55	25.00/3.5	49280lb/94psi	597kg/1285lb	T/L	-