

REM-28S



(L3/G3/MCS) LOADER/GRADER/ MOBILE CRANE SERVICE TIRE

The REM-28S is designed with a universal tread pattern for increased traction and performance in winter conditions. Its multiple application use includes loader, grader and on-highway, high speed mobile crane wheel positions.

★★★ Star product DOT certified for on-highway use



PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	TIRE WEIGHT	TIRE TYPE	NOTE
1117208952	385/95R25	REM-28S	★★★	70	43	54	16	31	10.00/1.5	13200lb/131psi	135kg/298lb	T/L	-
1107300251	17.5R25	REM-28S	★★	50	30	53	18	34	14.00/1.5	11990lb/76psi	157kg/338lb	T/L	-
1107300251	17.5R25	REM-28S	★★	10	5	53	18	34	14.00/1.5	18700lb/94psi	152kg/335lb	T/L	-
1107300751	20.5R25	REM-28S	★★	50	30	58	21	39	17.00/2.0	16100lb/76psi	231kg/491lb	T/L	-
1107300751	20.5R25	REM-28S	★★	10	5	58	21	39	17.00/2.0	25353lb/94psi	231kg/491lb	T/L	-
1107303251	23.5R25	REM-28S	★★	50	30	64	24	45	19.50/2.5	20400lb/76psi	231kg/491lb	T/L	-
1107303251	23.5R25	REM-28S	★★	10	5	64	24	45	19.50/2.5	32000lb/94psi	231kg/491lb	T/L	-
1107308951	385/95R24	REM-28S	★★	50	30	54	16	31	10.00W	11400lb/102psi	133kg/293lb	T/L	-