

# RR680



## PREMIUM REGIONAL/ALL-POSITION STEER TIRE

- Micro sipes on the groove edges prevent the onset of irregular wear.
- Premium 5-rib tread design with wide shoulders provides for durability and even wear in regional steer/all position applications.
- SmartWay California CARB compliant tread compounds for lower rolling resistance and better fuel economy.



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT (LB)
1133671255	11R22.5	14	G	144/142	L	41.4	11.1	18	8.25	6175lb/105psi	5840lb/105psi	19.8	499	115
1133671256	11R22.5	16	H	148/145	L	41.4	11.1	18	8.25	6940lb/123psi	6390lb/123psi	19.8	499	118
1133679255	295/75R22.5	14	G	144/141	M	40.6	11.7	18	9.00	6175lb/110psi	5675lb/110psi	19.5	504	118
TBA	295/75R22.5	16	H	146/143	M	40.4	11.7	18	9.00	6610lb/120psi	6005lb/120psi	18.9	518	112
1133671455	11R24.5	14	G	146/143	L	43.3	10.9	18	8.25	6610lb/105psi	6005lb/105psi	20.8	476	129
1133671456	11R24.5	16	H	149/146	L	43.3	10.9	18	8.25	7160lb/120psi	6610lb/120psi	20.8	476	132
1133678455	285/75R24.5	14	G	144/141	L	41.5	11.0	18	8.25	6175lb/110psi	5675lb/110psi	19.5	492	124
1133679214	9R22.5	14	G	136/134	L	38.3	9.1	18	6.75	4940lb/120psi	4675lb/120psi	17.9	206	110
1133679256	295/80R22.5	16	H	150/147	M	41.3	11.9	18	9.00	7390lb/120psi	6780lb/120psi	19.8	491	120
1133679258	295/80R22.5	18	J	152/149	M	41.3	11.9	18	9.00	7830lb/130psi	7160lb/130psi	19.8	491	120
1133671258	315/80R22.5	20	L	157/154	L	42.4	12.2	18	9.00	9090lb/130psi	8270lb/130psi	19.9	488	142
1133670456	305/75R24.5	16	H	154/149	M	42.7	11.6	19	9.00	8270lb/123psi	7160lb/123psi	20.8	516	145



Line Haul



Work



Regional



All-Season/Terrain



Fuel Efficient (SmartWay®)



Double Coin manufactures EPA SmartWay®-verified technologies