

RT500



PREMIUM LOW PROFILE ALL-POSITION MULTI-USE TIRE

- Special compounds used to deliver exceptional mileage in a variety of specialty trailer applications.
- Solid shoulders with unique waved siping added to the ribs help fight irregular wear, leading to better performance.
- Durable casing design with 4 steel belts provides protection from hazards leading to more uptime.



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT (LB)
1132598256	8.25R15TR	14	G	129/127	K	33.2	9.1	16	6.50	4080lb/120psi	3860lb/120psi	15.4	627	57
1132598257	8.25R15TR	18	J	143/141	K	33.2	9.1	16	6.50	6005lb/123psi	5675lb/123psi	15.4	627	57
1132591056	10.00R15TR	16	H	141/139	L	36.3	10.8	16	7.50	5675lb/120psi	5355lb/120psi	17.0	570	70
1132591057	10.00R15TR	18	J	148/145	K	36.3	10.8	16	7.50	6940lb/123psi	6390lb/123psi	17.0	570	70
1132697565	7.50R16LT	14	G	122/118	L	31.7	8.3	16	6.00G	3305lb/112psi	2910lb/112psi	14.6	662	56
1133391783	8R17.5	10	E	118/116	L	30.9	8.2	16	6.00	2910lb/95psi	2755lb/95psi	14.3	675	59
1133391706	10R17.5	16	H	143/141	L	33.9	9.8	16	7.50HC	6005lb/123psi	5675lb/123psi	15.8	613	79
1133391776	215/75R17.5	16	H	61/133	K	30.4	8.5	16	6.00	4805lb/125psi	4540lb/125psi	14.0	692	61
1133396797	235/75R17.5	18	J	143/141	L	31.6	9.1	16	6.75	6010lb/125psi	5680lb/125psi	14.7	662	72
1133394778	245/70R17.5	18	J	143/141	J	31.1	9.9	17	7.50	6005lb/127psi	5675lb/127psi	14.5	680	65
1133390894	8R19.5	12	F	124/122	M	34.1	8.2	16	6.00	3525lb/110psi	3305lb/110psi	16.3	592	69
1133396796	265/70R19.5	16	H	143/141	K	34.3	10.0	16	7.50	6010lb/125psi	5670lb/125psi	15.9	606	89
TBA	255/70R22.5	16	H	140/137	N	36.6	10.0	16	7.50	5510lb/120psi	5070lb/115psi	17.1	572	88
1133395727*	255/70R22.5	16	H	140/137	N	36.6	10.0	16	7.50	5510lb/115psi	5070lb/115psi	17.4	560	87
1133395726	255/70R22.5	16	H	140/137	N	36.6	10.0	16	7.50	5510lb/115psi	5070lb/115psi	17.4	560	87
1133397726	275/70R22.5	16	H	148/145	M	37.8	10.6	16	8.25	6930lb/131psi	6380lb/131psi	17.7	543	104
1133398796	285/70R19.5	16	H	145/143	M	35.2	11.0	16	8.25	6390lb/123psi	6010lb/123psi	16.2	590	93

* Cut/chip compound



Line Haul



Work



Regional



All-Season/Terrain



Fuel Efficient (SmartWay®)



Double Coin manufactures EPA SmartWay®-verified technologies