

RLB980



PREMIUM ALL-PURPOSE ALL-POSITION TIRE

- Aggressive multi-purpose tread design ideal for on/off highway applications.
- Center siping in the tread elements bite the road surface for improved traction and stability.
- Inter-block tie bars keep the tread stable even as the tire wears.
- Semi-open outside shoulder for superior evacuation of mud, soft soil, and water.

EXPLORE



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/ PRESSURE	DUAL MAX LOAD/ PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT	TYPE
1133968258	385/65R22.5	20	L	160	K	42.3	14.8	23	11.75	9920lb/130psi	N/A	19.8	495	168lb/76kg	TL
1133962258	425/65R22.5	20	L	165	K	44.6	16.5	23	12.25	11400lb/120psi	N/A	20.5	469	200lb/90kg	TL
1133962548	445/65R22.5	20	L	168	K	45.3	17.4	23	13.00	12300lb/120psi	N/A	20.9	457	220lb/100kg	TL

