

# RR905

## PREMIUM WIDE ALL-POSITION TIRE

- Innovative circumferential zig-zag grooves channel out water, providing excellent traction.
- Robust shoulder design keeps the tread stable, minimizing wear.
- Wider tread elements at the base prevent debris from penetrating the casing, preserving longevity.

**EXPLORE**



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT	TYPE
1133608258	385/65R22.5	20	L	160	J	42.0	15.0	20	11.80	9920lb/130psi	N/A	19.4	495	167lb/75kg	TL
1133603557	435/50R19.5	18	J	156	J	36.9	17.2	14	14.00	8820lb/123psi	N/A	16.9	550	161lb/73kg	TL
1133603558	435/50R19.5	20	L	160	J	36.9	17.2	14	14.00	9920lb/130psi	N/A	16.9	550	154lb/70kg	TL
1133608197	385/55R19.5	18	J	156	J	36.4	15.0	20	12.25	8820lb/130psi	N/A	16.9	560	135lb/61kg	TL
1133604558	445/45R19.5	20	L	160	K	36.4	17.6	17	15.00	9920lb/130psi	N/A	16.7	554	149lb/67kg	TL
1133608255	385/55R22.5	20	L	160	J	39.2	14.8	20	12.25	9920lb/130psi	N/A	17.5	499	148lb/67kg	TL