

RT606+



ULTRA PREMIUM 5-RIB REGIONAL STEER/ALL-POSITION TIRE

- Innovative zigzag siping and cut grooves combine to provide excellent traction and long even wear.
- Deep tread design for our best performance in regional steer/all position applications.
- Solid shoulder designed to keep the tread face stable during contact with the road surface for premium removal mileage.

EXPLORE



| PRODUCT CODE | TIRE SIZE | PLY RATING | LOAD RANGE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAM. (IN) | SECTION WIDTH (IN) | TREAD DEPTH (32NDS) | RIM | SINGLE MAX LOAD/PRESSURE | DUAL MAX LOAD/PRESSURE | STATIC LOAD RADIUS | REVS PER MILE | WEIGHT | TYPE |
|--------------|-------------|------------|------------|------------|--------------|--------------------|--------------------|---------------------|------|--------------------------|------------------------|--------------------|---------------|------------|------|
| 1136071255 | 11R22.5 | 14 | G | 144/142 | L | 41.6 | 11.1 | 22 | 8.25 | 6175lb/105psi | 5840lb/105psi | 19.8 | 496 | 123lb/56kg | TL |
| 1136071256 | 11R22.5 | 16 | H | 148/145 | L | 41.6 | 11.1 | 22 | 8.25 | 6940lb/123psi | 6390lb/123psi | 19.8 | 496 | 125lb/57kg | TL |
| 1136079255 | 295/75R22.5 | 14 | G | 144/141 | L | 40.7 | 11.7 | 22 | 9.00 | 6175lb/110psi | 5675lb/110psi | 19.5 | 496 | 129lb/58kg | TL |
| 1136071455 | 11R24.5 | 14 | G | 146/143 | L | 43.5 | 10.9 | 22 | 8.25 | 6610lb/105psi | 6005lb/105psi | 20.8 | 473 | 137lb/61kg | TL |
| 1136071456 | 11R24.5 | 16 | H | 149/146 | L | 43.5 | 10.9 | 22 | 8.25 | 7160lb/120psi | 6610lb/120psi | 20.8 | 473 | 139lb/63kg | TL |
| 1136078455 | 285/75R24.5 | 14 | G | 144/141 | L | 41.5 | 10.6 | 22 | 8.25 | 6175lb/110psi | 5675lb/110psi | 19.5 | 492 | 129lb/58kg | TL |