

# RLB452



## ULTRA PREMIUM OPEN SHOULDER DRIVE-POSITION TIRE

- Robust casing design with stone ejectors preserves the casing, maximizing service life.
- Offset shoulder blocks with ties keep the tread stable, providing long tread life.
- Deep original tread for higher removal mileage.

EXPLORE



| PRODUCT CODE | TIRE SIZE   | PLY RATING | LOAD RANGE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAM. (IN) | SECTION WIDTH (IN) | TREAD DEPTH (32NDS) | RIM  | SINGLE MAX LOAD/ PRESSURE | DUAL MAX LOAD/ PRESSURE | STATIC LOAD RADIUS | REVS PER MILE | WEIGHT     | TYPE |
|--------------|-------------|------------|------------|------------|--------------|--------------------|--------------------|---------------------|------|---------------------------|-------------------------|--------------------|---------------|------------|------|
| 1133621255   | 11R22.5     | 14         | G          | 144/142    | L            | 41.9               | 11.1               | 28                  | 8.25 | 6175lb/105psi             | 5840lb/105psi           | 19.6               | 496           | 129lb/58kg | TL   |
| 1133621256   | 11R22.5     | 16         | H          | 148/145    | L            | 41.9               | 11.1               | 28                  | 8.25 | 6940lb/123psi             | 6390lb/123psi           | 19.6               | 496           | 132lb/60kg | TL   |
| 1133629255   | 295/75R22.5 | 14         | G          | 144/141    | L            | 41.1               | 11.9               | 28                  | 9.00 | 6175lb/110psi             | 5675lb/110psi           | 19.3               | 505           | 131lb/59kg | TL   |
| 1133629257   | 295/75R22.5 | 16         | H          | 146/143    | J            | 41.1               | 11.9               | 28                  | 9.00 | 6610lb/120psi             | 6005lb/120psi           | 19.2               | 506           | 131lb/59kg | TL   |
| 1133621455   | 11R24.5     | 14         | G          | 146/143    | L            | 43.6               | 10.9               | 28                  | 8.25 | 6610lb/105psi             | 6005lb/105psi           | 20.1               | 476           | 138lb/62kg | TL   |
| 1133621456   | 11R24.5     | 16         | H          | 149/146    | L            | 43.6               | 10.9               | 28                  | 8.25 | 7160lb/120psi             | 6610lb/120psi           | 20.1               | 476           | 141lb/64kg | TL   |
| 1133628455   | 285/75R24.5 | 14         | G          | 144/141    | L            | 41.2               | 10.9               | 28                  | 8.25 | 6175lb/110psi             | 5675lb/110psi           | 19.6               | 493           | 131lb/59kg | TL   |
| 1133628457   | 285/75R24.5 | 16         | H          | 147/144    | K            | 41.2               | 10.9               | 28                  | 8.25 | 6780lb/120psi             | 6175lb/120psi           | 19.6               | 493           | 131lb/59kg | TL   |