

RR680



OptiGreen Series

PREMIUM REGIONAL/ALL-POSITION TIRE

- Micro sipes on the groove edges prevent the onset of irregular wear.
- Premium 5-rib tread design with wide shoulders provides for durability and even wear in regional steer/all position applications.
- SmartWay® California CARB compliant tread compounds for lower rolling resistance and better fuel economy.

EXPLORE



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/ PRESSURE	DUAL MAX LOAD/ PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT	TYPE
1133671255	11R22.5	14	G	144/142	L	41.4	11.1	18.5	8.25	6175lb/105psi	5840lb/105psi	19.8	499	114lb/51kg	TL
1133671256	11R22.5	16	H	148/145	L	41.4	11.1	18.5	8.25	6940lb/123psi	6390lb/123psi	19.8	499	119lb/54kg	TL
1133679255	295/75R22.5	14	G	144/141	M	40.6	11.7	18	9.00	6175lb/110psi	5675lb/110psi	19.5	504	118lb/54kg	TL
1133679257	295/75R22.5	16	H	146/143	M	40.6	11.7	18	9.00	6610lb/120psi	6005lb/120psi	18.9	518	121lb/55kg	TL
1133671455	11R24.5	14	G	146/143	L	43.3	10.9	18.5	8.25	6610lb/105psi	6005lb/105psi	20.8	476	128lb/58kg	TL
1133671456	11R24.5	16	H	149/146	L	43.3	10.9	18.5	8.25	7160lb/120psi	6610lb/120psi	20.8	476	60lb/133kg	TL
1133678455	285/75R24.5	14	G	144/141	L	41.5	11.0	18	8.25	6175lb/110psi	5675lb/110psi	19.5	492	123lb/55kg	TL
1133679214	9R22.5	14	G	136/134	L	38.3	9.1	18.5	6.75	4940lb/120psi	4675lb/120psi	17.9	206	111lb/50kg	TL
1133679258	295/80R22.5	18	J	152/149	M	41.3	11.9	18	9.00	7830lb/130psi	7160lb/130psi	19.8	491	120lb/54kg	TL
1133671258	315/80R22.5	20	L	157/154	L	42.4	12.4	18	9	9090lb/130psi	8270lb/130psi	19.9	488	142lb/64kg	TL
1133670457*	305/75R24.5	18	J	154/149	M	42.7	11.6	19	9.00	8267lb/123psi	7165lb/123psi	19.6	486	138lb/63kg	TL

* The redesigned RT600+ for 6.0"/6.75" rim sizes



www.DoubleCoinTires.com