

RR905



PREMIUM WIDE ALL-POSITION TIRE

- Innovative circumferential zig-zag grooves channel out water, providing excellent traction.
- Robust shoulder design keeps the tread stable, minimizing wear.
- Wider tread elements at the base prevent debris from penetrating the casing, preserving longevity.

EXPLORE



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/ PRESSURE	DUAL MAX LOAD/ PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT	TYPE
1133608258	385/65R22.5	20	L	160	J	42.0	15.0	20	11.80	9920lb/130psi	N/A	19.4	495	167lb/75kg	TL
1133603557	435/50R19.5	18	J	156	J	36.8	17.2	17.5	14.00	8820lb/123psi	N/A	16.9	550	154lb/70kg	TL
1133603558	435/50R19.5	20	L	160	J	36.8	17.2	17.5	14.00	9920lb/130psi	N/A	16.9	550	154lb/70kg	TL
1133608197	385/55R19.5	18	J	156	J	36.4	15.0	20	12.25	8820lb/130psi	N/A	16.9	560	135lb/61kg	TL
1133604558	445/45R19.5	20	L	160	J	35.4	17.5	17	15.00	9920lb/135psi	N/A	16.7	554	149lb/67kg	TL
1133608255	385/55R22.5	20	L	160	J	39.2	14.8	20	12.25	9920lb/135psi	N/A	17.5	499	148lb/67kg	TL