

RR99



PREMIUM ON/OFF HIGHWAY MIXED SERVICE ALL-POSITION TIRE

- Strong all-position tread pattern designed for multiple on/off highway uses.
- Outside shoulder grooves with zigzag center grooves provide added traction in mud and soft soil.

EXPLORE



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/ PRESSURE	DUAL MAX LOAD/ PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT	TYPE
1133437565	7.50R16	14	G	122/118	L	31.9	8.3	16	6.00	3305lb/112psi	2910lb/112psi	14.7	656	59lb/27kg	TT
1133991256	11R22.5	16	H	148/145	L	41.3	10.9	21.5	8.25	6940lb/123psi	6390lb/123psi	19.5	496	124lb/56kg	TL
1133991456	11R24.5	16	H	149/146	L	43.4	10.9	21.5	8.25	7160lb/120psi	6610lb/120psi	21	484	131lb/59kg	TL
1133992256	12R22.5	16	H	152/148	L	42.7	11.8	21.5	9.00	7830lb/120psi	6940lb/120psi	20.1	516	135lb/61kg	TL
1133992258	12R22.5	18	J	152/149	L	42.7	11.8	21.5	9.00	7830lb/61psi	7160lb/61psi	20.1	516	135lb/61kg	TL
1133433227	13R22.5	18	J	154/151	M	43.9	12.2	21.5	9.75	8270lb/123psi	7610lb/123psi	20.7	465	164lb/74kg	TL
1133991257	315/80R22.5	18	J	156/152	L	42.7	12.4	19	9.00	8820lb/120psi	7830lb/120psi	19.9	484	144lb/66kg	TL
1133991259	315/80R22.5	22	M	160/157	J/65MPH	42.7	12.4	19	9.00	10000lb/130psi	9090lb/130psi	19.9	483	149lb/67kg	TL
1133439205	9.00R20	14	G	141/139	M	40.2	10.1	19	7.00	5675lb/115psi	5355lb/115psi	18.9	510	111lb/50kg	TT

