

RLB452



ULTRA PREMIUM OPEN SHOULDER DRIVE-POSITION TIRE

- Robust casing design with stone ejectors preserves the casing, maximizing service life.
- Offset shoulder blocks with ties keep the tread stable, providing long tread life.
- Deep original tread for higher removal mileage.



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT (LB)	TYPE
1133621255	11R22.5	14	G	144/142	L	41.9	11.1	28	8.25	6175lb/105psi	5840lb/105psi	19.6	496	130	TL
1133621256	11R22.5	16	H	148/145	L	41.9	11.1	28	8.25	6940lb/123psi	6390lb/123psi	19.6	496	130	TL
1133629255	295/75R22.5	14	G	144/141	L	41.0	11.7	28	9.00	6175lb/110psi	5675lb/110psi	19.2	506	129	TL
1133629257	295/75R22.5	16	H	146/143	J	41.0	11.7	28	9.00	6610lb/120psi	6005lb/120psi	19.2	506	129	TL
1133621455	11R24.5	14	G	146/143	L	43.6	10.9	28	8.25	6610lb/105psi	6005lb/105psi	20.1	476	135	TL
1133621456	11R24.5	16	H	149/146	L	43.6	10.9	28	8.25	7160lb/120psi	6610lb/120psi	20.1	476	137	TL
1133628455	285/75R24.5	14	G	144/141	L	42.2	11.1	28	8.25	6175lb/110psi	5675lb/110psi	19.6	493	131	TL
1133628457	285/75R24.5	16	H	147/144	K	42.2	11.1	28	8.25	6780lb/120psi	6175lb/120psi	19.6	493	131	TL