

RLB450

OPEN SHOULDER DRIVE-POSITION TIRE

- Innovative open shoulder tread design provides outstanding traction and delivers even wear.
- Heavy-duty casings provide strength and stability, and promote retreadability.
- Deep tread depth provides excellent wear in long and short haul applications.



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT (LB)	TYPE
1133611255	11R22.5	14	G	144/142	L	41.9	10.9	25	8.25	6175lb/105psi	5840lb/105psi	19.8	493	120	TL
1133611256	11R22.5	16	H	148/145	L	41.9	10.9	25	8.25	6940lb/120psi	6390lb/120psi	19.8	493	125	TL
1133619253	295/60R22.5	16	H	150/147	L	36.5	11.5	24	9.00	7390lb/130psi	6780lb/130psi	17.4	560	125	TL
1133619255	295/75R22.5	14	G	144/141	L	40.8	11.4	24	9.00	6175lb/110psi	5675lb/110psi	19.4	495	128	TL
1133619258	295/80R22.5	18	J	152/149	M	41.8	11.7	29	9.00	7830lb/130psi	7160lb/130psi	19.8	493	130	TL
1133611455	11R24.5	14	G	146/143	L	41.7	10.9	25	8.25	6610lb/105psi	6005lb/105psi	19.8	471	134	TL
1133611456	11R24.5	16	H	149/146	L	41.7	10.9	25	8.25	7160lb/120psi	6610lb/120psi	19.8	471	137	TL
1133618455	285/75R24.5	14	G	144/141	L	41.9	11.0	24	8.25	6175lb/110psi	5675lb/100psi	19.8	485	127	TL
1133611258	315/80R22.5	18	J	156/150	L	43.2	12.5	29	9.00	8820lb/123psi	7385lb/123psi	21.0	480	161	TL
1133611259	315/80R22.5	20	L	157/154	J	43.2	12.5	29	9.00	9090lb/130psi	8270lb/130psi	21.0	480	161	TL
1133611406	11.00R22	16	H	152/149	K	45.4	11.6	30	8.00	7830lb/130psi	7160lb/120psi	21.2	466	134	TT