

RLB490



LOW PROFILE DRIVE-POSITION MULTI-USE TIRE

- Innovative tread design and compounds provide long, even wear.
- Circumferential siping provides evacuation of water and debris leading to better tread contact with the road surface.
- Closed shoulder design keeps the tread stable while alternating tread blocks grip the road surface for a mix of long service life and driver confidence.



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT (LB)	TYPE
1134902796	225/70R19.5	14	G	128/126	N	32.5	8.8	19	6.75	3970lb/110psi	3750lb/110psi	15.8	635	68	TL
1134904796	245/70R19.5	16	H	136/134	K	33.5	9.6	19	7.50	4940lb/120psi	4675lb/120psi	15.2	617	84	TL
1134906796	265/70R19.5	16	H	143/141	K	34.6	10.0	22	7.50	6010lb/125psi	5670lb/125psi	16.4	615	93	TL
1134905726	255/70R22.5	16	H	140/137	L	37.0	10.0	22	7.50	5510lb/120psi	5070lb/120psi	17.0	597	96	TL
1134907726	275/70R22.5	16	H	148/145	K	38.1	11.0	22	8.25	6930lb/131psi	6380lb/131psi	17.7	543	112	TL