

FR605

OptiGreen Series



FUEL EFFICIENT STEER-POSITION TIRE

- Extensive siping and defense grooves in the tread provide even wear while maintaining excellent traction.
- Circumferential equalizer ribs help to distribute force by spreading the load across the face of the tire leading to more even wear.
- Fuel efficient compound for lower rolling resistance.



| PRODUCT CODE | TIRE SIZE | PLY RATING | LOAD RANGE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAM. (IN) | SECTION WIDTH (IN) | TREAD DEPTH (32NDS) | RIM | SINGLE MAX LOAD/PRESSURE | DUAL MAX LOAD/PRESSURE | STATIC LOAD RADIUS | REVS PER MILE | WEIGHT (LB) | TYPE |
|--------------|-------------|------------|------------|------------|--------------|--------------------|--------------------|---------------------|------|--------------------------|------------------------|--------------------|---------------|-------------|------|
| 1133771255 | 11R22.5 | 14 | G | 144/142 | M | 41.4 | 11.1 | 17 | 8.25 | 6175lb/105psi | 5840lb/105psi | 19.8 | 496 | 113 | TL |
| 1133771256 | 11R22.5 | 16 | H | 148/145 | M | 41.4 | 11.1 | 17 | 8.25 | 6940lb/123psi | 6390lb/123psi | 19.8 | 496 | 117 | TL |
| 1133779255 | 295/75R22.5 | 14 | G | 144/141 | M | 40.6 | 11.7 | 17 | 9.00 | 6175lb/110psi | 5675lb/110psi | 18.8 | 510 | 108 | TL |
| 1133771455 | 11R24.5 | 14 | G | 146/143 | M | 43.3 | 10.9 | 17 | 8.25 | 6610lb/105psi | 6005lb/105psi | 20.8 | 473 | 125 | TL |
| 1133771456 | 11R24.5 | 16 | H | 149/146 | M | 43.3 | 10.9 | 17 | 8.25 | 7160lb/120psi | 6610lb/120psi | 20.8 | 473 | 128 | TL |
| 1133778455 | 285/75R24.5 | 14 | G | 144/141 | M | 41.5 | 11.0 | 17 | 8.25 | 6175lb/110psi | 5675lb/110psi | 19.5 | 492 | 124 | TL |