

REM-9



(E4) HAULAGE TIRE

The Double Coin REM-9 OTR radial design offers special compounds to withstand severe mining applications, extend tire life and promote long-term retreadability. The REM-9 OTR tire is designed with a non-directional center rib tread pattern for enhanced off-the-road traction. Its deep tread depth also provides extended tread life in a wide variety of conditions.

EXPLORE



PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	WEIGHT	TYPE
1087206255**	26.5R25	REM-9 (A)	★★	50 10	30 5	70	27	69	22.00/3.0	25300lb/76psi 40700lb/94psi	1191lb/540kg	TL
1087202958**	29.5R25	REM-9 (A)	★★	50 10	30 5	75	30	76	25.00/3.5	30800lb/76psi 49280lb/94psi	1434lb/650kg	TL

****E4/L4**

PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	WEIGHT	TYPE
1087201833	18.00R33	REM-9 (A)	★★	50	30	73	20	69	13.00/2.5	23980lb/102psi	1037lb/470kg	TL
1087201834	18.00R33	REM-9 (S)	★★	50	30	73	20	69	13.00/2.5	23980lb/102psi	1037lb/470kg	TL
1087201835	18.00R33	REM-9 (B)	★★	50	30	73	20	69	13.00/2.5	23980lb/102psi	1037lb/470kg	TL
1087202452	24.00R35	REM-9 (A)	★★	50	30	85	26	87	17.00/3.5	40700lb/102psi	1713lb/777kg	TL
1087202453	24.00R35	REM-9 (S)	★★	50	30	85	26	87	17.00/3.5	40700lb/102psi	1713lb/777kg	TL
1087202454	24.00R35	REM-9 (B)	★★	50	30	85	26	87	17.00/3.5	40700lb/102psi	1713lb/777kg	TL
1087202135	21.00R33	REM-9 (B)	★★	50	30	77	22	69	15.00/3.0	30864lb/102psi	1251lb/567kg	TL

Compounds: **A** cut/chip; **S** standard; **B** heat