

RR99/RR9*



PREMIUM ON/OFF HIGHWAY MIXED SERVICE ALL-POSITION TIRE

- Strong all-position tread pattern designed for multiple on/off highway uses.
- Outside shoulder grooves with zigzag center grooves provide added traction in mud and soft soil.



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT (LB)	TYPE
1133437565	7.50R16	14	G	122/118	L	31.9	8.3	16	6.00	3305lb/112psi	2910lb/112psi	14.7	656	59	TT
1133991256	11R22.5	16	H	148/145	L	41.3	10.9	19	8.25	6940lb/123psi	6390lb/123psi	19.5	496	123	TL
1133991456	11R24.5	16	H	149/146	L	43.4	10.9	21	8.25	7160lb/120psi	6610lb/120psi	21	484	131	TL
1133992256	12R22.5	16	H	152/148	L	42.7	11.8	21	9.00	7830lb/120psi	6940lb/120psi	20.1	516	134	TL
1133992258	12R22.5	18	J	152/149	L	42.7	11.8	21	9.00	7830lb/61psi	7160lb/61psi	20.1	516	134	TL
1133433227	13R22.5	18	J	154/151	M	43.9	12.2	20	9.75	8270lb/123psi	7610lb/123psi	20.7	465	164	TL
1133991257	315/80R22.5	18	J	156/152	L	42.7	12.4	19	9.00	8820lb/120psi	7830lb/120psi	19.9	484	145	TL
1133991258	315/80R22.5	20	L	157/154	L	42.4	12.2	19	9.00	9090lb/130psi	8270lb/130psi	19.9	483	147	TL
1133991259	315/80R22.5	22	M	160/157	65MPH	42.4	12.2	20	9.00	10000lb/130psi	9090lb/130psi	19.9	483	147	TL
1133439205	9.00R20	14	G	141/139	M	40.2	10.1	19	7.00	5675lb/115psi	5355lb/115psi	18.9	510	110	TT
1133431026*	10.00R20	16	H	146/143	K	41.3	10.7	20	7.50	6610lb/120psi	6005lb/120psi	19.4	497	140	TT
1133431206*	11.00R20	16	H	150/147	K	42.7	11.1	20	8.00	7390lb/120psi	6780lb/120psi	20.1	478	155	TT
1133432207*	12.00R20	18	J	154/151	L	44	11.7	20	8.50	8270lb/120psi	7610lb/120psi	20.6	466	164	TT